

Severtson Box Speakers

Dual 5 1/4" Center Channel Speaker SEV-5252BC



- Impedance: 8 Ohms
- Frequency Response: 65 Hz - 20,000 Hz
- Power Handling Capacity: 60 Watts Nominal and 120 Watts Maximum
- Woofer: 5 1/4" Woven Kevlar Cone Woofer. 10 oz Magnet X 2
- Rubber Surround
- Tweeter:: 1" Silk Dome with 8 oz Ferrite Magnet
- Sensitivity: 90 dB
- Overall Dimension: 6 1/2" T x 17 5/8" W x 7" D
- 2—Flush Mounting Brackets & 2—1/4-20 threaded holes for Mounting Arm Brackets
- Accepts Banana Plugs

5 1/4" Box Speaker Pair SEV-52BS



- Impedance: 8 Ohms
- Frequency Response: 65 Hz - 20,000 Hz
- Power Handling Capacity: 60 Watts Nominal and 120 Watts Maximum
- Woofer: 5 1/4" Woven Kevlar Cone Woofer. 10 oz Magnet
- Rubber Surround
- Tweeter:: 1" Silk Dome with 8 oz Ferrite Magnet
- Sensitivity: 88 dB
- Overall Dimension: 11 1/2" T x 6 1/2" W x 7" D
- 2—Flush Mounting Brackets & 2—1/4-20 threaded holes for Mounting Arm Brackets
- Accepts Banana Plugs

Dual 6 1/2" Tower Speaker Pair SEV-6565TS



- Impedance: 8 Ohms
- Frequency Response: 45 Hz - 20,000 Hz
- Power Handling Capacity: 80 Watts Nominal and 160 Watts Maximum
- Woofer: 6 1/2" Woven Kevlar Cone Woofer. 17 oz Magnet X 2
- Rubber Surround
- Tweeter:: 1" Silk Dome with 8 oz Ferrite Magnet
- Sensitivity: 91 dB
- Overall Dimension: 39 1/2" T x 8" W x 9 3/4" D
- Accepts 2 Pair of Banana Plugs, 1 pair in & 1 Pair through

12" 300 Watt Powered Subwoofer SEV-SUB12



- Impedance: 4 Ohms \pm 15%
- Frequency Response: 30 Hz - 3,000 Hz
- Woofer: 12" Cone Woofer. 41 oz Magnet
- Rubber Surround
- Tweeter: No
- Sensitivity: 90 \pm 3dB
- Overall Dimension: 20" T x 14" W x 17" D
- Shipping Weight: 45 lbs.

6 1/2" 3-Way Dual Voice Coil Stereo In-Ceiling Speaker SEV-S62C



- Single Speaker with two lines in for stereo capabilities - Dual Voice Coil - 2 Channel. Great for bathrooms and hallways where you want stereo sound, but two speakers don't fit or look pleasing. Run one line in for a 3-way 6 1/2" speaker.
- Flip Lever Quick Mount System
- Grills, Screws, Hole Cut-Out Templates, and Paint Masks Included
- Impedance: 8 Ohms
- Frequency Response: 43 Hz - 20,000 Hz
- Power Handling Capacity: 80 Watts Nominal and 160 Watts Maximum per each channel
- Woofer: 6 1/2" Woven Kevlar Cone Woofer. 10 oz Magnet
- Rubber Surround
- Tweeter:: 1" Titanium Silk Membrane Dome Pivoting
- Sensitivity: 89 \pm 2 dB
- Crossover: 12 dB per Octave
- Cut-Out Dimension: 8"
- Overall Dimension: 9 3/4"

Recommendations For your speakers



- If you are looking for a package or whole house audio—give us a call for package pricing.
- If wiring a new home don't forget to use rough in kits to save time.
- See speaker wall plates for a clean professional install.
- For large speaker order request special pricing.